

Oreshnik IRBM: A Case Study in Resilient Multi-Layer Guidance Architecture Combining INS and GLONASS Corrections in GNSS-Degraded Environment

by Marco Lisi

The operational employment of Russia's Oreshnik intermediate-range ballistic missile (IRBM) provides valuable insights into hybrid navigation systems, specifically the integration of inertial navigation systems (INS) with GNSS corrections in contested electromagnetic environments. This case highlights key aspects of sensor fusion, drift management, and mission resilience in satellite-denied or jammed scenarios, topics of significant interest to the geomatics, positioning, navigation, and timing (PNT) communities.

Operational Demonstrations

Russia has conducted at least two confirmed operational uses of the Oreshnik. The first took place on 21 November 2024, when the missile was launched from the Kapustin Yar test range and struck the Dnipro area (likely targeting the Pivdenmash industrial complex). The second occurred on the night of 8–9 January 2026, again launched from Kapustin Yar, hitting infrastructure in Lviv Oblast, western Ukraine, near the Polish border.

In both instances, the missile carried inert/kinetic (non-explosive) warheads (reportedly consisting of multiple submunitions) and caused limited physical damage with no reported casualties. Ukrainian air defense systems, including Patriot batteries, failed to detect or intercept the incoming missile. While these strikes served



clear demonstrative and deterrent purposes, they offered rare real-world observations of an IRBM operating in a contested theater.

Technical Characteristics

The Oreshnik is a two-stage, solid-propellant, road-mobile IRBM deployed from a transporter-erector-launcher (TEL). It has an estimated operational range of 3,000 to 5,500 km and reaches hypersonic speeds exceeding Mach 10 (approximately 12,000–13,000 km/h) during the re-entry phase. This performance enables it to reach major European capitals in a matter of minutes.

The missile supports both conventional and nuclear payloads. It features Multiple Independently Targetable Reentry Vehicles (MIRV) capability, with up to six reentry vehicles and a total payload mass of roughly 1.3–1.5 tons. Each reentry vehicle can be independently targeted, allowing a single launch to engage multiple dispersed objectives. The primary strategic role emphasizes regional deterrence, rapid deep strikes, and saturation of defenses rather than ultra-precise point targeting.

Guidance Architecture: INS Primary with Opportunistic GLONASS Corrections

The Oreshnik employs a robust multi-layer guidance system in which a high-precision inertial navigation system (INS), based on advanced gyroscopes and accelerometers, serves as the primary and autonomous core. The INS continuously integrates accelerations and angular rates to estimate position, velocity, and attitude without emitting signals or relying on external inputs, making it inherently resistant to jamming and spoofing.

The principal limitation of any INS is drift—the gradual accumulation of small sensor errors that increases the Circular Error Probable (CEP) over time. For an IRBM with a flight time of only tens of minutes, military-grade inertial sensors keep this drift within limits acceptable for strategic or area-effect missions.

Russia's GLONASS satellite navigation system acts as a secondary correction layer, primarily during the boost and mid-course phases, to periodically update and reduce INS drift when signals are available. The architecture includes clear fallback mechanisms: in the event of jamming, spoofing, or inconsistent satellite data, the system automatically reverts to pure inertial navigation without compromising the mission.

Military-grade GLONASS receivers likely incorporate encrypted signals, anti-spoofing algorithm-

ms, directional antennas, and advanced sensor-fusion techniques (such as Kalman filtering or adaptive weighting) that dynamically evaluate the reliability of each data source. In the terminal phase, emphasis shifts to high velocity, stability, and evasive maneuvers designed to overwhelm or penetrate missile defense systems rather than achieve maximum accuracy.

Strategic and Geospatial Implications

The Oreshnik's guidance philosophy prioritizes operational resilience over extreme precision, aligning with its role as a theater-level deterrent capable of functioning effectively in GNSS-denied environments. For the broader geomatics and PNT community, the missile exemplifies mature INS/GNSS hybridization, robust fault detection in sensor fusion, and the continued strategic importance of inertial systems as a reliable backbone in electronic warfare scenarios. These principles have direct parallels in civilian applications such as autonomous vehicles, precision timing, and surveying in contested or remote areas.

Conclusion

The Oreshnik demonstrates how modern ballistic missiles can achieve credible performance through layered, resilient navigation architectures. Its emphasis on INS autonomy combined with opportunistic satellite updates illustrates key technological trends in PNT resilience that will influence both military and dual-use positioning systems in the coming years.

ABSTRACT

Operational demonstrations of the Russian Oreshnik IRBM illustrate resilient multi-layer guidance through primary inertial navigation (INS) supplemented by GLONASS corrections. Designed to manage drift and maintain effectiveness under jamming or spoofing, the system offers practical lessons in sensor fusion and PNT resilience relevant to military and civilian geomatics applications.

KEYWORDS

INS; GNSS; GLONASS; SENSOR FUSION; JAMMING; SPOOFING; IRBM; PNT RESILIENCE; ELECTRONIC WARFARE

AUTHOR

PROF. ING. MARCO LISI
MARCO.LISI@ASI.IT
MARCO.LISI@ESTERI.IT
SPECIAL ENVOY FOR SPACE OF THE ITALIAN MINISTRY OF FOREIGN AFFAIRS
BOARD MEMBER AT ITALIAN SPACE AGENCY (ASI)
AEROSPACE & DEFENSE CONSULTANT